

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 581
IDENTITY: CLEAR LUBE II + 20A Revision Date: 09/15/2009

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

| Name | Cas No. | OSHA PEL | ACGIH TLV | OTHER LIM | % |
|--------------------------|------------|----------|-----------|-----------|-------|
| HEPTANE | 142-82-5 | 400 PPM | 400 PPM | N/A | _____ |
| ISOPARAFINIC HYDROCARBON | 64742-47-8 | 400 PPM | 400 PPM | | _____ |
| PROPANE/N-BUTANE | 68476-86-8 | N/A | 1000ppm | N/A | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |
| _____ | _____ | _____ | _____ | _____ | _____ |

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 156 Specific Gravity (water=1) 0.79
Vapor Pressure (mm Hg) 40 Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: N/A
Solubility in Water: 0% (Butyl Acetate=1)
Appearance and Odor: TACKY GELLED LUBRICANT, SOLVENT ODOR.

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): <100F TCC Flammable Limits: LEL: 1.1 UEL: 7.5
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS. FLAMMABLE.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 581

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F
Stable: X
Incompatibility (Materials to Avoid): NONE KNOWN

Hazardous Decomposition or Byproducts: OXIDES OF CARBON

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: DIZZINESS-PROLONGED MAY LEAD TO UNCONSCIOUSNESS. EYES: STRONG IRRITATION, REDDENING. SKIN: MILD IRRITATION MAY CAUSE LOCALIZED DEFATTING
INGESTION: NAUSEA, DISSINESS, VOMITING, INTESTINAL CRAMPING.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE
WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING.
CONTACT PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYES:
FLUSH WITH WATER AND CONTACT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. WRAP CONTAINER IN OLD RAGS AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS.
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GOGGLES RECOMMENDED
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
N/A

□