

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 346
IDENTITY: RED HOT + 20A Revision Date: 08/09/2010

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Contains entries for ISOPARAFINIC HYDROCARBON and PROPANE/N-BUTANE.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 212 F Specific Gravity (water=1) 0.98
Vapor Pressure (mm Hg) >17 Melting Point: N/A
Vapor Density (AIR=1) <0.7 Evaporation Rate: <1
Solubility in Water: 65% (Butyl Acetate=1)
Appearance and Odor: FINE MIST, CINNAMON SCENT

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): >200F TCC Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE.
EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 346

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F, HOT SURFACES
Incompatibility (Materials to Avoid): Strong oxidizers

Hazardous Decomposition or Byproducts: oxides of carbon

Hazardous Polymerization: May Occur: Will Not Occur: XX
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: WILL CAUSE DIZZINESS IF INHALED DIRECTLY OR EXPOSED TO
EXCESSIVE AMOUNTS. EYES: MAY CAUSE IRRITATION AND REDDENING. SKIN: MAY
CAUSE LOCALIZED IRRITATION. INGESTION: MAY CAUSE NAUSEA.
Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE.

Medical Conditions Generally Aggravated by Exposure: NONE

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CONSULT
PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF
IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER. INGESTION: DRINK
SEVERAL GLASSES OF WATER. CONSULT PHYSICIAN IF NEEDED.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE AN ABSORBENT CLAY FOR LARGE SPILLS. DISPOSE OF RESIDUE IN ACCORDANCE
WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT, SPARKS, FIRE OR OPEN FLAME.

Other Precautions: EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.
DO NOT PUNCTURE OR INCINERATE. VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA.
Ventilation: Local Exhaust:N/A
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves:N/A
Eye Protection: SAFETY GLASSES RECOMMENDED WHEN USING CHEMICAL PRODUCTS
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USE

□