

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 291
IDENTITY: GRIP + QT Revision Date: 01/20/2010

Section I

Manufacturer's Name: MAINTENANCE SOLUTIONS*** ^ Telephone Numbers:
Address: P.O. BOX 12202 Emergency:
800/255-3924
SCOTTSDALE Information:
State: AZ Zip Code: 85267 800/747-9593

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %, and a blank column. Row 1: PHOSPHORIC ACID, *, 7664-38-2, 1 MG/M3, 1 MG/M3, N/A, ____.

Comment:
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 212+ Specific Gravity (water=1) 1.10
Vapor Pressure (mm Hg) 18 Melting Point: N/A
Vapor Density (AIR=1) >1 Evaporation Rate: <.01
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: CLEAR TO HAZY LIQUID WITH CHERRY SCENT.

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point (Method Used): NONE Flammable Limits: LEL: N/A UEL: N/A
Extinguishing Media: NONE
Special Fire Fighting Procedures: NONE

Unusual Fire and Explosion Hazards: CONTACT WITH SOME METALS, PARTICULARLY
MAGNESIUM, ALUMINUM AND GALVANIZED ZINC CAN GENERATE HYDROGEN RAPIDLY WHICH
IS EXPLOSIVE.

