

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 238
IDENTITY: STRIP-EZE Revision Date: 03/09/2010

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 1 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 212 Specific Gravity (water=1) 0.99
Vapor Pressure(mm Hg) 17.5 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 100%. (Butyl Acetate=1)
Appearance and Odor: WHITE FOAM, SLIGHT AMMONIA ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS
WHEN INDICATED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 238

=====
Stability: Unstable: Conditions to avoid:
 Stable: X TEMPERATURES ABOVE 120 F
Incompatibility (Materials to Avoid): SOME PAINTED SURFACES.

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

=====
Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INGESTION: NAUSEA, SICKNESS. INHALATION: DIZZINESS. EYES: MAY CAUSE SEVERE
IRRITATION. SKIN: WILL CAUSE IRRITATION, BURNING.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INGESTIONS: GIVE 1-2 GLASSES OF WATER.
CALL PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. INHALATION: REMOVE
TO FRESH AIR. EYES: FLUSH WITH PLENTY OF WATER AND CONSULT PHYSICIAN.
SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

=====
Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: WRAP CONTAINER AND PLACE IN TRASH COLLECTION.
DO NOT PUNCTURE OR INCINERATE. OFFER FOR RECYCLING IF POSSIBLE
DO NOT REUSE CONTAINER.

Precautions to be Taken in Handling and Storing: KEEP AWAY FROM CHILDREN.
STORE IN A COOL DRY AREA. KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME.

Other Precautions: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE
TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

=====
Respiratory Protection: NONE
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: RECOMMENDED
Eye Protection: SAFETY GLASSES ARE REQUIRED WHEN USING THIS PRODUCT
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS AFTER USING